

TLV Type: Structure (Anonymous)					
InvokeRequests		Context Tag	2	Array of CommandDataIB	-

NOTE

In this version of the specification, InvokeRequestMessage contains no provisions for spanning multiple messages (see [Section 4.4.4, “Message Size Requirements”](#)).

10.7.10. InvokeResponseMessage

NOTE

The interaction model is written at the abstract level of actions, and as such, it does not address fragmentation. The interaction model describes a complete response to the invoke interaction as a unit, the chunking protocol described here maintains that illusion as much as possible. The status response messages (Status = SUCCESS) are used for flow control. Status response messages with any other Status indicate the sender of any further chunked InvokeResponseMessages must exit early. In exiting early, the sender MAY send an InvalidAction StatusResponse.

TLV Type: Structure (Anonymous)					
Element	Comments	Tag Type	Tag Number	Type	Range
SuppressResponse		Context Tag	0	Boolean	-
InvokeResponses		Context Tag	1	Array of InvokeResponseIB	-
MoreChunkedMessages		Context Tag	2	Boolean	-

10.7.10.1. SuppressResponse

- If MoreChunkedMessages is true, SuppressResponse SHALL be false.
- If MoreChunkedMessages is false, SuppressResponse SHALL be set to the SuppressResponse value in the Invoke Response action being encoded.

10.7.10.2. InvokeResponses

If the InvokeResponseMessage is being generated in response to an InvokeRequestMessage containing InvokeRequests of length 1, it SHALL contain an InvokeResponses element, and it SHALL NOT contain MoreChunkedMessages.

10.7.10.3. MoreChunkedMessages

Multiple InvokeResponseMessages MAY be sent in a single transaction when multiple CommandDataIBs were present in the Invoke Request action. All but the last message SHALL have the MoreChunkedMessages flag set to true to indicate this situation, and the last message SHALL have the MoreChunkedMessages flag set to false.

Implementations MAY choose to send the InvokeResponseMessage at any granularity, such as: