

11.1.5.17. LocalConfigDisabled Attribute

This attribute SHALL allow a local Node configuration to be disabled. When this attribute is set to True the Node SHALL disable the ability to configure the Node through an on-Node user interface. The value of the LocalConfigDisabled attribute SHALL NOT in any way modify, disable, or otherwise affect the user’s ability to trigger a factory reset on the Node.

11.1.5.18. Reachable Attribute

This attribute (when used) SHALL indicate whether the Node can be reached. For a native Node this is implicitly True (and its use is optional). Its main use case is in the derived [Bridged Device Basic Information](#) cluster where it is used to indicate whether the bridged device is reachable by the bridge over the non-native network.

11.1.5.19. UniqueID Attribute

This attribute SHALL indicate a unique identifier for the device, which is constructed in a manufacturer specific manner. It MAY be constructed using a permanent device identifier (such as device MAC address) as basis. In order to prevent tracking,

- it SHOULD NOT be identical to (or easily derived from) such permanent device identifier
- it SHALL be updated when the device is factory reset
- it SHALL NOT be identical to the SerialNumber attribute
- it SHALL NOT be printed on the product or delivered with the product

The value does not need to be human readable, since it is intended for machine to machine (M2M) communication.

NOTE	The conformance of the UniqueID attribute was optional in cluster revisions prior to revision 4.
NOTE	This UniqueID attribute SHALL NOT be the same as the Persistent Unique ID which is used in the Rotating Device Identifier mechanism.

11.1.5.20. CapabilityMinima Attribute

This attribute SHALL provide the minimum guaranteed value for some system-wide resource capabilities that are not otherwise cluster-specific and do not appear elsewhere. This attribute MAY be used by clients to optimize communication with Nodes by allowing them to use more than the strict minimum values required by this specification, wherever available.

The values supported by the server in reality MAY be larger than the values provided in this attribute, such as if a server is not resource-constrained at all. However, clients SHOULD only rely on the amounts provided in this attribute.

Note that since the fixed values within this attribute MAY change over time, both increasing and decreasing, as software versions change for a given Node, clients SHOULD take care not to assume