

Value	Name	Summary	Conformance
1	CacheAndSync	Message counter synchronization using cache-and-sync	CS

11.2.5.2. GroupKeyMulticastPolicyEnum Type

This data type is derived from [enum8](#).

Value	Name	Summary	Conformance
0	PerGroupID	Indicates filtering of multicast messages for a specific Group ID	M
1	AllNodes	Indicates not filtering of multicast messages	M

PerGroupID Value

The 16-bit Group Identifier of the Multicast Address SHALL be the Group ID of the group.

AllNodes Value

The 16-bit Group Identifier of the Multicast Address SHALL be 0xFFFF.

11.2.5.3. GroupKeyMapStruct Type

Access Modifier: Fabric Scoped							
ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
1	GroupId	group-id	all				M
2	GroupKey-SetID	uint16	1 to 65535				M

GroupId Field

This field uniquely identifies the group within the scope of the given Fabric.

GroupKeySetID Field

This field references the set of group keys that generate operational group keys for use with this group, as specified in [Section 4.17.3.5.1, “Group Key Set ID”](#).

A GroupKeyMapStruct SHALL NOT accept GroupKeySetID of 0, which is reserved for the [IPK](#).

11.2.5.4. GroupKeySetStruct Type