

EpochStartTime0 Field

This field, if not null, SHALL define when EpochKey0 becomes valid as specified by [Section 4.17.3, “Epoch Keys”](#). Units are absolute UTC time in microseconds encoded using the [epoch-us](#) representation.

EpochKey1 Field

This field, if not null, SHALL be the root credential used in the derivation of an operational group key for epoch slot 1 of the given group key set. If EpochKey1 is not null, EpochStartTime1 SHALL NOT be null.

EpochStartTime1 Field

This field, if not null, SHALL define when EpochKey1 becomes valid as specified by [Section 4.17.3, “Epoch Keys”](#). Units are absolute UTC time in microseconds encoded using the [epoch-us](#) representation.

EpochKey2 Field

This field, if not null, SHALL be the root credential used in the derivation of an operational group key for epoch slot 2 of the given group key set. If EpochKey2 is not null, EpochStartTime2 SHALL NOT be null.

EpochStartTime2 Field

This field, if not null, SHALL define when EpochKey2 becomes valid as specified by [Section 4.17.3, “Epoch Keys”](#). Units are absolute UTC time in microseconds encoded using the [epoch-us](#) representation.

GroupKeyMulticastPolicy Field

This field specifies how the [IPv6 Multicast Address](#) SHALL be formed for groups using this operational group key set.

The PerGroupID method maximizes filtering of multicast messages, so that receiving nodes receive only multicast messages for groups to which they are subscribed.

The AllNodes method minimizes the number of multicast addresses to which a receiver node needs to subscribe.

NOTE

Support for GroupKeyMulticastPolicy is provisional. Correct default behavior is that implied by value PerGroupID.

11.2.5.5. GroupInfoMapStruct Type

Access Modifier: Fabric Scoped							
ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
1	GroupId	group-id	all				M