

Access Modifier: Fabric Scoped							
2	Endpoints	list[endpoint-no]	min 1				M
3	Group-Name	string	max 16				O

GroupId Field

This field uniquely identifies the group within the scope of the given Fabric.

Endpoints Field

This field provides the list of Endpoint IDs on the Node to which messages to this group SHALL be forwarded.

GroupName Field

This field provides a name for the group. This field SHALL contain the last GroupName written for a given GroupId on any Endpoint via the Groups cluster.

11.2.6. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	Group-KeyMap	list[GroupKeyMapStruct]	desc	N	empty	RW VM F	M
0x0001	GroupTable	list[GroupInfoMapStruct]	desc		empty	R V F	M
0x0002	Max-GroupsPerFabric	uint16	all	F	0	R V	M
0x0003	Max-Group-KeysPer-Fabric	uint16	1 to 65535	F	1	R V	M

11.2.6.1. GroupKeyMap Attribute

This attribute is a list of [GroupKeyMapStruct](#) entries. Each entry associates a logical Group Id with a particular group key set.

11.2.6.2. GroupTable Attribute

This attribute is a list of [GroupInfoMapStruct](#) entries. Each entry provides read-only information about how a given logical Group ID maps to a particular set of endpoints, and a name for the group.