

11.3.4.1. ActiveLocale Attribute

The ActiveLocale attribute SHALL represent the locale that the Node is currently configured to use when conveying information. The ActiveLocale attribute SHALL be a Language Tag as defined by [BCP47](#). The ActiveLocale attribute SHALL have a default value assigned by the Vendor and SHALL be a value contained within the SupportedLocales attribute.

An attempt to write a value to ActiveLocale that is not present in SupportedLocales SHALL result in a CONSTRAINT_ERROR error.

11.3.4.2. SupportedLocales Attribute

The SupportedLocales attribute SHALL represent a list of locale strings that are valid values for the [ActiveLocale](#) attribute. The list SHALL NOT contain any duplicate entries. The ordering of items within the list SHOULD NOT express any meaning.

11.4. Time Format Localization Cluster

Nodes should be expected to be deployed to any and all regions of the world. These global regions may have differing preferences for how dates and times are conveyed. As such, Nodes that visually or audibly convey time information need a mechanism by which they can be configured to use a user’s preferred format.

This cluster supports an interface to a Node. It provides attributes for determining and configuring time and date formatting information that a Node SHALL utilize when conveying values to a user.

11.4.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial revision

11.4.2. Classification

Hierarchy	Role	Scope	PICS Code
Base	Utility	Node	LTIME

11.4.3. Cluster ID

ID	Name
0x002C	Time Format Localization

11.4.4. Features

This cluster SHALL support the FeatureMap bitmap attribute as defined below.