

tion level while retaining the underlying representation.

XPAN ID is a big-endian 64-bit unsigned number, represented on the first 8 octets of the octet string.

Connected Field

This field SHALL indicate the connected status of the associated network, where "connected" means currently linked to the network technology (e.g. Associated for a Wi-Fi network, media connected for an Ethernet network).

11.9.5.6. WiFiInterfaceScanResultStruct Type

WiFiInterfaceScanResultStruct represents a single Wi-Fi network scan result.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	Security	WiFiSecurityBitmap	all				WI
1	SSID	octstr	max 32				WI
2	BSSID	octstr	6				WI
3	Channel	uint16	all				WI
4	WiFiBand	WiFiBandEnum	all				[WI]
5	RSSI	int8	all				[WI]

WiFiBand Field

This field, if present, MAY be used to differentiate overlapping channel number values across different Wi-Fi frequency bands.

RSSI Field

This field, if present, SHALL denote the signal strength in dBm of the associated scan result.

11.9.5.7. ThreadInterfaceScanResultStruct Type

ThreadInterfaceScanResultStruct represents a single Thread network scan result.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	PanId	uint16	max 65534				TH
1	Extended-PanId	uint64	all				TH
2	Network-Name	string	1 to 16				TH
3	Channel	uint16	all				TH