

Breadcrumb Field

See [Section 11.9.7.1.2, “Breadcrumb Field”](#) for usage.

11.9.7.7. NetworkConfigResponse Command

This command is used to report the results of a network configuration command (AddOrUpdateWiFiNetwork, AddOrUpdateThreadNetwork, or RemoveNetwork).

This response command relates status information for some commands which require it as their response command. See each individual cluster server command for the situations that may cause a NetworkingStatus different than Success.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	NetworkingStatus	Network-CommissioningStatusEnum	desc			M
1	DebugText	string	max 512			O
2	NetworkIndex	uint8	max (MaxNetworks - 1)			NetworkingStatus == Success

Before generating a NetworkConfigResponse, the server SHALL set the [LastNetworkingStatus](#) attribute value to the NetworkingStatus matching the response.

Before generating a NetworkConfigResponse, the server SHALL set the [LastNetworkID](#) attribute value to the NetworkID that was used in the command for which an invocation caused the response to be generated.

NetworkingStatus Field

The NetworkingStatus field SHALL indicate the status of the last operation attempting to modify the [Networks](#) attribute configuration, taking one of these values:

- Success: Operation succeeded.
- [OutOfRange](#): Network identifier was invalid (e.g. empty, too long, etc).
- [BoundsExceeded](#): Adding this network configuration would exceed the limit defined by [MaxNetworks](#).
- [NetworkIdNotFound](#): The network identifier was expected to be found, but was not found among the added network configurations in [Networks](#) attribute.
- [UnknownError](#): An internal error occurred during the operation.

DebugText Field

See [Section 11.9.7.2.2, “DebugText Field”](#) for usage.