

11.10.6.3. RegulatoryConfig Attribute

This attribute SHALL indicate the regulatory configuration for the product.

Note that the country code is part of [Section 11.1, “Basic Information Cluster”](#) and therefore NOT listed on the RegulatoryConfig attribute.

11.10.6.4. LocationCapability Attribute

LocationCapability is statically set by the manufacturer and indicates if this Node needs to be told an exact RegulatoryLocation. For example a Node which is "Indoor Only" would not be certified for outdoor use at all, and thus there is no need for a commissioner to set or ask the user about whether the device will be used inside or outside. However a device which states its capability is "Indoor/Outdoor" means it would like clarification if possible.

For Nodes without radio network interfaces (e.g. Ethernet-only devices), the value IndoorOutdoor SHALL always be used.

The default value of the [RegulatoryConfig](#) attribute is the value of LocationCapability attribute. This means devices always have a safe default value, and Commissioners which choose to implement smarter handling can.

11.10.6.5. SupportsConcurrentConnection Attribute

This attribute SHALL indicate whether this device supports "concurrent connection flow" commissioning mode (see [Section 5.5, “Commissioning Flows”](#)). If false, the device only supports "non-concurrent connection flow" mode.

11.10.6.6. TCAcceptedVersion Attribute

This attribute SHALL indicate the last version of the T&Cs for which the device received user acknowledgements. On factory reset this field SHALL be reset to 0.

When [Custom Commissioning Flow](#) is used to obtain user consent (e. g. because the Commissioner does not support the TC feature), the manufacturer-provided means for obtaining user consent SHALL ensure that this attribute is set to a value which is greater than or equal to [TCMinRequiredVersion](#) before returning the user back to the originating Commissioner (see [Section 5.7.4, “Enhanced Setup Flow \(ESF\)”](#)).

11.10.6.7. TCMinRequiredVersion Attribute

This attribute SHALL indicate the minimum version of the texts presented by the Enhanced Setup Flow that need to be accepted by the user for this device. This attribute MAY change as the result of an OTA update.

If an event such as a software update causes TCAcceptedVersion to become less than TCMinRequiredVersion, then the device SHALL update [TCAcknowledgementsRequired](#) to True so that an administrator can detect that a newer version of the texts needs to be presented to the user.