

An ErrorCode of [NoFailSafe](#) SHALL be responded to the invoker if the CommissioningComplete command was received when no [Fail-Safe context](#) exists.

If [Terms and Conditions](#) are required, then an ErrorCode of [TCAcknowledgementsNotReceived](#) SHALL be responded to the invoker if the user acknowledgements to the required Terms and Conditions have not been provided.

This command is fabric-scoped, so cannot be issued over a session that does not have an associated fabric, i.e. over PASE session prior to an AddNOC command. In addition, this command is only permitted over CASE and must be issued by a node associated with the ongoing Fail-Safe context. An ErrorCode of [InvalidAuthentication](#) SHALL be responded to the invoker if the CommissioningComplete command was received outside a [CASE](#) session (e.g., over Group messaging, or [PASE](#) session after AddNOC), or if the accessing fabric is not the one associated with the ongoing Fail-Safe context.

This command SHALL only result in success with an ErrorCode value of OK in the [CommissioningCompleteResponse](#) if received over a [CASE](#) session and the [accessing fabric index](#) matches the Fabric Index associated with the current Fail-Safe context. In other words:

- If no AddNOC command had been successfully invoked, the CommissioningComplete command must originate from the Fabric that initiated the Fail-Safe context.
- After an AddNOC command has been successfully invoked, the CommissioningComplete command must originate from the Fabric which was joined through the execution of that command, which updated the Fail-Safe context's Fabric Index.

On successful execution of the CommissioningComplete command, where the CommissioningCompleteResponse has an ErrorCode of OK, the following actions SHALL be undertaken on the Server:

1. The [Fail-Safe timer](#) associated with the current Fail-Safe context SHALL be disarmed.
2. The commissioning window at the Server SHALL be closed.
3. Any temporary administrative privileges automatically granted to any open [PASE](#) session SHALL be revoked (see [Section 6.6.2.9, "Bootstrapping of the Access Control Cluster"](#)).
4. The [Secure Session Context](#) of any [PASE](#) session still established at the Server SHALL be cleared.
5. The [Breadcrumb](#) attribute SHALL be reset to zero.

After receipt of a CommissioningCompleteResponse with an ErrorCode value of OK, a client cannot expect any previously established [PASE](#) session to still be usable, due to the server having cleared such sessions.

11.10.7.7. CommissioningCompleteResponse Command

This command is used to report the result of the CommissioningComplete command.