

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	ErrorCode	CommissioningErrorEnum			OK	M
1	DebugText	string			""	M

ErrorCode Field

This field SHALL contain the result of the operation, based on the behavior specified in the functional description of the CommissioningComplete command.

DebugText Field

See [Section 11.10.7.1, “Common fields in General Commissioning cluster responses”](#).

11.10.7.8. SetTCAcknowledgements Command

This command is used to set the user acknowledgements received in the Enhanced Setup Flow Terms & Conditions into the node.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	TCVersion	uint16	all			M
1	TCUserResponse	map16	all			M

TCVersion field

This field SHALL contain the version of the Enhanced Setup Flow Terms & Conditions that were presented to the user.

TCUserResponse field

This field SHALL contain the user responses to the Enhanced Setup Flow Terms & Conditions as a map where each bit set in the bitmap corresponds to an accepted term in the file located at [Section 11.23.6.22, “EnhancedSetupFlowTCUrl”](#).

Effect on Receipt

This command SHALL copy the user responses and accepted version to the presented Enhanced Setup Flow Terms & Conditions from the values provided in the TCUserResponse and TCVersion fields to the [TCAcknowledgements Attribute](#) and the [TCAcceptedVersion Attribute](#) fields respectively.

This command SHALL result in success with an ErrorCode value of OK in the [SetTCAcknowledgementsResponse](#) if all required terms were accepted by the user. Specifically, all bits have a value of 1 in TCAcknowledgements whose ordinal is marked as required in the file located at [EnhancedSe-](#)