

[tupFlowTCUrl](#).

If the TCVersion field is less than the [TCMinRequiredVersion](#), then the ErrorCode of [TCMinVersion-NotMet](#) SHALL be returned and [TCAcknowledgements](#) SHALL remain unchanged.

If TCVersion is greater than or equal to TCMinRequiredVersion, but the TCUserResponse value indicates that not all required terms were accepted by the user, then the ErrorCode of [RequiredTCNotAccepted](#) SHALL be returned and [TCAcknowledgements](#) SHALL remain unchanged.

11.10.7.9. SetTCAcknowledgementsResponse Command

This command is used to report the result of the SetTCAcknowledgements command.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	ErrorCode	CommissioningErrorEnum			OK	M

ErrorCode Field

This field SHALL contain the result of the operation, based on the behavior specified in the [functional description of the SetTCAcknowledgements command](#).

11.11. Diagnostic Logs Cluster

This Cluster supports an interface to a Node. It provides commands for retrieving unstructured diagnostic logs from a Node that may be used to aid in diagnostics. It will often be the case that unstructured diagnostic logs will be Node-wide and not specific to any subset of Endpoints. When present, this Cluster SHALL be implemented once for the Node. The Node SHOULD also implement the BDX Initiator and BDX Sender roles as defined in the [BDX Protocol](#).

11.11.1. Revision History

The global ClusterRevision Attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial revision

11.11.2. Classification

Hierarchy	Role	Scope	PICS Code	Quality
Base	Utility	Node	DLOG	K