

LQI Field

This field SHALL specify the implementation specific mix of IEEE 802.15.4 PDU receive quality indicators, scaled from 0 to 255.

AverageRssi Field

This field SHOULD specify the average RSSI across all received frames from the neighboring Node since the receiving Node's last reboot. If there is no known received frames this field SHOULD have the value of null. This field SHALL have the units of dBm, having the range -128 dBm to 0 dBm.

LastRssi Field

This field SHALL specify the RSSI of the most recently received frame from the neighboring Node. If there is no known last received frame the LastRssi field SHOULD have the value of null. This field SHALL have the units of dBm, having the range -128 dBm to 0 dBm.

FrameErrorRate Field

This field SHALL specify the percentage of received frames from the neighboring Node that have resulted in errors.

MessageErrorRate Field

This field SHALL specify the percentage of received messages from the neighboring Node that have resulted in errors.

RxOnWhenIdle Field

This field SHALL specify if the neighboring Node is capable of receiving frames while the Node is in an idle state.

FullThreadDevice Field

This field SHALL specify if the neighboring Node is a full Thread device.

FullNetworkData Field

This field SHALL specify if the neighboring Node requires the full Network Data. If set to False, the neighboring Node only requires the stable Network Data.

IsChild Field

This field SHALL specify if the neighboring Node is a direct child of the Node reporting the [NeighborTable](#) attribute.

11.14.5.5. RouteTableStruct Type