

cators, scaled from 0 to 255, from the perspective of the Node reporting the neighbor table.

LQIOut Field

This field SHALL specify the implementation specific mix of IEEE 802.15.4 PDU receive quality indicators, scaled from 0 to 255, from the perspective of the Node specified within the NextHop field.

Age Field

This field SHALL specify the duration of time, in seconds, since a frame has been received from the Node for which this route table entry corresponds.

Allocated Field

This field SHALL specify if the router ID as defined within the RouterId field has been allocated.

LinkEstablished Field

This field SHALL specify if a link has been established to the Node for which this route table entry corresponds.

11.14.5.6. SecurityPolicy Type

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	Rotation-Time	uint16					M
1	Flags	uint16					M

RotationTime Field

This field SHALL specify the interval of time, in hours, that Thread security keys are rotated. This attribute SHALL be null when there is no dataset configured.

Flags Field

This field SHALL specify the flags as specified in Thread 1.3.0 section 8.10.1.15. This attribute SHALL be null when there is no dataset configured.

11.14.5.7. OperationalDatasetComponents Type

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	Active-Time-stampPresent	bool					M