

- If the `TrustedTimeSource` field in the command is null, the node SHALL set the `TrustedTimeSource` attribute to null and SHALL generate a [MissingTrustedTimeSource](#) event.
- Otherwise, the node SHALL set the `TrustedTimeSource` attribute to a struct which has `NodeID` and `Endpoint` fields matching those in the `TrustedTimeSource` field and has its `FabricIndex` field set to the command's [accessing fabric index](#).

Access Modifier: Fabric Scoped						
ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Trusted-TimeSource	FabricScope-dTrusted-Time-SourceStruct		X		M

TrustedTimeSource Field

This field contains the Node ID and endpoint of a trusted time source on the accessing fabric.

11.17.9.3. SetTimeZone Command

This command is used to set the time zone of the node. The data for this command is as follows:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	TimeZone	list[TimeZoneStruct]	1 to 2			M

If the given list is larger than the `TimeZoneListMaxSize`, the node SHALL respond with `RESOURCE_EXHAUSTED` and the `TimeZone` attribute SHALL NOT be updated.

If the given list does not conform to the list requirements in [TimeZone](#) attribute the node SHALL respond with a `CONSTRAINT_ERROR` and the `TimeZone` attribute SHALL NOT be updated.

If there are no errors in the list, the `TimeZone` field SHALL be copied to the `TimeZone` attribute. A [TimeZoneStatus](#) event SHALL be generated with the new time zone information.

If the node supports a time zone database and it has information available for the time zone that will be applied, it MAY set its [DSTOffset](#) attribute, otherwise the [DSTOffset](#) attribute SHALL be set to an empty list. A [DSTTableEmpty](#) event SHALL be generated if the [DSTOffset](#) attribute is empty. A [DSTStatus](#) event SHALL be generated if the node was previously applying a DST offset.

11.17.9.4. SetTimeZoneResponse Command

This command is used to report the result of a `SetTimeZone` command. This command SHALL be generated in response to a `SetTimeZone` command.