

description.

11.17.10. Events

ID	Name	Priority	Quality	Access	Conformance
0x00	DST-TableEmpty	INFO		V	TZ
0x01	DSTStatus	INFO		V	TZ
0x02	TimeZoneStatus	INFO		V	TZ
0x03	TimeFailure	INFO		V	M
0x04	MissingTrustedTimeSource	INFO		V	TSC

11.17.10.1. DSTTableEmpty Event

This event SHALL be generated when the node stops applying the current DSTOffset and there are no entries in the list with a larger ValidStarting time, indicating the need to possibly get new DST data. This event SHALL also be generated if the DSTOffset list is cleared either by a [SetTimeZone](#) command, or by a [SetDSTOffset](#) command with an empty list.

The node SHALL generate this event if the node has not generated a DSTTableEmpty event in the last hour, and the DSTOffset list is empty when the node attempts to update its time. DST-TableEmpty events corresponding to a time update SHOULD NOT be generated more often than once per hour.

There is no data for this event.

11.17.10.2. DSTStatus Event

This event SHALL be generated when the node starts or stops applying a DST offset.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	DSTOffsetActive	bool				M

DSTOffsetActive Field

Indicates whether the current DST offset is being applied (i.e, daylight savings time is applied, as opposed to standard time).

11.17.10.3. TimeZoneStatus Event

This event SHALL be generated when the node changes its time zone offset or name. It SHALL NOT be sent for DST changes that are not accompanied by a time zone change.