

| Revision | Description                                                                                                                                                                                                    |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1        | Initial revision                                                                                                                                                                                               |
| 2        | Introduction of command, attributes and fields to support the <a href="#">Fabric Table Vendor ID Verification Procedure</a> . The procedure increased flash storage cost by approximately 90 bytes per fabric. |

**NOTE**

The name was re-normalized from "Node Operational Credentials" cluster to "Operational Credentials" cluster in Matter 1.4.2, to match much of the implementation legacy that used the latter name.

### 11.18.2. Classification

| Hierarchy | Role    | Scope | PICS Code |
|-----------|---------|-------|-----------|
| Base      | Utility | Node  | OPCREDS   |

### 11.18.3. Cluster ID

| ID     | Name                    |
|--------|-------------------------|
| 0x003E | Operational Credentials |

### 11.18.4. Data Types

#### 11.18.4.1. RESP\_MAX Constant Type

A RESP\_MAX constant appears in the description of some command fields in this cluster and within the description of some associated serialization schemes.

The value RESP\_MAX SHALL be 900 bytes.

The current limit of 900 bytes was chosen to accommodate the maximum size of IPv6 frames, transport headers, message layer headers and integrity protection and Interaction Model protocol encoding, while accounting for sufficient remaining space for signatures and to allow extensions to larger key and digest sizes in the future.

#### 11.18.4.2. CertificateChainTypeEnum Type

This data type is derived from [enum8](#).

This enumeration is used by the [CertificateChainRequest](#) command to convey which certificate from the device attestation certificate chain to transmit back to the client.

| Value | Name                  | Summary                                 | Conformance |
|-------|-----------------------|-----------------------------------------|-------------|
| 1     | <b>DACCertificate</b> | Request the DER-encoded DAC certificate | M           |