

If no commissioning window was open at time of receipt, this command SHALL fail with a cluster specific status code of WindowNotOpen.

If the commissioning window was open and the fail-safe was armed when this command is received, the device SHALL immediately expire the fail-safe and perform the cleanup steps outlined in [Section 11.10.7.2.2, "Behavior on expiry of Fail-Safe timer"](#).

11.20. Over-the-Air (OTA) Software Update

11.20.1. Scope & Purpose

The majority of IoT devices require security and/or functional feature updates during their lifetime.

This section describes a set of OTA software update capabilities which enable an "OTA Requestor" to be informed of, obtain, and install software updates from a Node fulfilling the role of an "OTA Provider".

An "OTA Requestor" is any Node implementing the OTA Requestor Device Type (0x0012), which fulfills the client role for the [OTA Software Update Provider cluster](#) and the server role for the [OTA Software Update Requestor cluster](#). An "OTA Provider" is any Node implementing the OTA Provider Device Type (0x0014), which fulfills the server role for the [OTA Software Update Provider cluster](#) and the client role for the [OTA Software Update Requestor cluster](#).

The OTA updates capabilities are designed to support:

- A mechanism to inform OTA Requestors about available OTA Providers.
- A mechanism to allow OTA Requestors to acquire information about available OTA Software Images.
- A mechanism to allow constrained OTA Requestors to obtain OTA Software Images through a local proxy, e.g. if they are not able or willing to proceed with a direct download from the Internet.
- A mechanism to allow OTA Requestors supporting legacy, non-native, or out-of-band update methods to notify an OTA Provider of having completed an update out-of-band.
- A mechanism to allow deferred installation of a software update, based on administrative rules.
- A mechanism to allow user consent to be considered before offering Software Images to OTA Requestors.

OTA Requestors wishing to update their software using these capabilities MAY need to use an application bootloader and MAY require sufficient additional storage in order to download an OTA image.

Furthermore, to encourage interoperability and timely software updates, the OTA update mechanisms provide means of obtaining Software Images which can be uniformly implemented across OTA Requestors on devices from a variety of different vendors. The OTA Providers SHOULD provide services to OTA Requestors from vendors other than its own, as long as the location of Software Update images for these vendors is found. The [Distributed Compliance Ledger](#) is one such centralized source of software update image locations that MAY allow OTA Providers to provide OTA Soft-