

```

Privilege: Operate,
AuthMode: CASE,
Subjects: [ <Node ID of the node implementing OTA Requestor cluster client> ],
Targets: [ <Endpoint hosting the OTA Requestor cluster server> ]
}

```

Commissioner or Administrator SHOULD install necessary ACL Entries at Commissioning time or later to enable processing of [QueryImage commands](#) from OTA Requestors on their Fabric, otherwise that OTA Provider will not be usable by OTA Requestors.

Below is an exemplary ACL entry for a Node implementing the OTA Provider cluster server to support the processing of the QueryImage command:

```

{
  FabricIndex: <Fabric Index of the fabric in question>,
  Privilege: Operate,
  AuthMode: CASE,
  Subjects: [ ], // Empty for "any" Node wildcard
  Targets: [ <Endpoint hosting the OTA Provider cluster server> ]
}

```

Note that there may be a variety of ACL entry configurations that fulfill the necessary goals, including wildcard entries for the Administrators on a given Fabric. The examples above are for illustration purposes only.

Handling UpdateAvailable value in Status field

The UpdateAvailable status indicates that the OTA Provider has an update available.

The remaining fields within the [QueryImageResponse](#) command SHALL contain the information necessary to allow the OTA Requestor to obtain an updated Software Image.

The field [ImageURI](#) SHALL be set to a location from where the image can be downloaded. The URI provided SHALL be for a protocol within the list of supported protocols provided in the request (see [Section 11.20.6.5.1.4, “ProtocolsSupported Field”](#)). Selection of the URI is based on the information available in the OTA Provider’s Software Images data set.

The field [UpdateToken](#) SHALL be populated by the OTA Provider with a value of its choosing, to allow tracking of the flow from a given OTA Requestor when it sends further requests. The valid length of the UpdateToken is between 8 and 32 bytes, inclusively. The token SHALL be recorded by the OTA Requestor, until an OTA Software Update Image is either applied or discarded. This value SHALL be provided to any subsequent ApplyUpdateRequest and NotifyUpdateApplied commands.

The field [SoftwareVersion](#) SHALL be set to the version number matching the new Software Image.

If the field [DelayedActionTime](#) is present, the OTA Requestor SHALL wait at least the indicated time before proceeding with the next step.