

ID	Name	Type	Constraint	Quality	Fallback	Conformance
2	Software-Version	uint32	all			M
3	ProtocolsSupported	list[DownloadProtocolEnum]	max 8			M
4	Hardware-Version	uint16	all			O
5	Location	string	2			O
6	Requestor-CanConsent	bool	all		False	O
7	Meta-dataFor-Provider	octstr	max 512			O

VendorID Field

The value SHALL be the Vendor ID applying to the OTA Requestor's Node and SHALL match the value reported by the [Basic Information Cluster VendorID](#) attribute.

ProductID Field

The value SHALL be the Product ID applying to the OTA Requestor's Node and SHALL match the value reported by the [Basic Information Cluster ProductID](#) attribute.

SoftwareVersion Field

The SoftwareVersion included in the request payload SHALL provide the value representing the current version running on the OTA Requestor invoking the command. This version SHALL be equal to the [Software Version attribute](#) of the [Basic Information Cluster](#).

ProtocolsSupported Field

This field SHALL contain a list of all download protocols supported by the OTA Requestor.

This field SHALL be used by the OTA Provider to generate the correct URI for the location of the Software Image when one is found to be available. BDX Synchronous transfer mode SHALL always be supported by an OTA Provider. Furthermore, OTA Providers with access to external networking SHOULD support the HTTPS protocol. OTA Providers MAY support other protocols.

The algorithm to select the specific protocol to use in a given Software Image URI is implementation-dependent, provided that the rules in [Section 11.20.3.3.1, "Download Protocol selection"](#) are followed.

See [Section 11.20.3.2, "Querying the OTA Provider"](#) and [Section 11.20.3.5, "Transfer of OTA Software Update images"](#) for more details about usage of this field.