

HardwareVersion Field

The value of this field, if present, SHALL contain the OTA Requestor's hardware version, and SHALL be equal to the [HardwareVersion attribute](#) of the [Basic Information Cluster](#).

Location Field

The location, if present, SHALL provide the same value as the [Basic Information Cluster Location attribute](#) for the OTA Requestor as configured. This MAY be used by the OTA Provider logic to allow per-region selection of the Software Image.

RequestorCanConsent Field

This field SHALL be set to true by an OTA Requestor that is capable of obtaining user consent for OTA application by virtue of built-in user interface capabilities. Otherwise, it SHALL be false.

See [Section 11.20.3.4, "Obtaining user consent for updating software"](#) for application details about usage.

MetadataForProvider Field

This optional field, if present, SHALL consist of a [top-level anonymous list](#); each list element SHALL have a [profile-specific](#) tag encoded in [fully-qualified](#) form. Each list element SHALL contain a manufacturer-specific payload, which the OTA Requestor invoking this command wants to expose to the receiving OTA Provider. This payload MAY be used for any purpose and SHOULD be as small as practical.

The use of this field SHOULD be restricted to Vendor-specific usage and SHALL NOT be used as a selector required to match for the selection of a Software Image in production environments, unless absolutely necessary, as the interpretation of this field may be ambiguous to OTA Providers implementing the Cluster in a compliant but divergent way from the sender.

An example of usage for this field is for an OTA Requestor to provide specific data about grouping or authentication in field trial environments, where the OTA Provider is likely to understand it and be able to act upon it, either for special selection of image, or recording of activity.

An OTA Provider SHALL report the availability of Software Images, if one is found to be applicable using the other provided fields, even if the MetadataForProvider field is deemed to contain invalid or unknown information. That is, the contents of the MetadataForProvider field SHALL NOT be used to deny a software update to an OTA Requestor, unless both OTA Requestor and OTA Provider have an externally agreed-upon policy whereby strictly correct additional MetadataForProvider is expected to fulfill the OTA Software Update process.

Usage of the QueryImage Command

OTA Requestors SHALL send a QueryImage command to the OTA Provider to determine the availability of a new Software Image.

See [Section 11.20.3.2, "Querying the OTA Provider"](#) for full details about the OTA Software Update Query flow which makes use of this command.