

QueryImageResponse Command

This command is sent in response to the [QueryImage](#) command.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Status	StatusEnum	all			M
1	DelayedActionTime	uint32	all		0	Status == Busy , 0
2	ImageURI	string	max 256			Status == UpdateAvailable
3	Software-Version	uint32	all			Status == UpdateAvailable
4	Software-Version-String	string	1 to 64			Status == UpdateAvailable
5	UpdateToken	octstr	8 to 32			Status == UpdateAvailable
6	UserConsentNeeded	bool	all		False	0
7	MetadataForRequestor	octstr	max 512			0

Status Field

This field SHALL contain the primary response regarding the availability of a Software Image.

See [Section 11.20.3.2, “Querying the OTA Provider”](#) for details about the possible values for this field and their meaning.

DelayedActionTime Field

This field SHALL be provided when the Status field is set to Busy, and MAY be provided in other cases. This field, if provided, SHALL convey the minimum time to wait, in seconds from the time of this response, before sending another QueryImage command or beginning a download from the OTA Provider. OTA Requestors SHALL respect this minimum delay, unless they had previously restarted and lost track of it. OTA Providers SHOULD expect OTA Requestors to follow this value to their best capability, however, a restarting Node MAY come back sooner, due to having lost track of this state response.

See [Section 11.20.3.2, “Querying the OTA Provider”](#) for details about the rules regarding this field.