

Status code value	Error	Description
0x0012	LENGTH_TOO_LARGE	Definite length too large to support. For example, trying to SendInit with too large of a file.
0x0013	LENGTH_TOO_SHORT	Definite length proposed for transfer is too short for the context based on the responder's knowledge of expected size.
0x0014	LENGTH_MISMATCH	Pre-negotiated size of transfer was not fulfilled prior to BlockAckEOF.
0x0015	LENGTH_REQUIRED	Responder can only support proposed transfer if definite length is provided.
0x0016	BAD_MESSAGE_CONTENTS	Received a malformed protocol message.
0x0017	BAD_BLOCK_COUNTER	Received block counter out of order from expectation.
0x0018	UNEXPECTED_MESSAGE	Received a well-formed message that was contextually inappropriate for the current state of the transfer.
0x0019	RESPONDER_BUSY	Responder is too busy to proceed with a new transfer at this moment.
0x001F	TRANSFER_FAILED_UNKNOWN_ERROR	Other error occurred, such as perhaps an input/output error occurring at one of the peers.
0x0050	TRANSFER_METHOD_NOT_SUPPORTED	Received a message that mismatches the current transfer mode.
0x0051	FILE_DESIGNATOR_UNKNOWN	Attempted to request a file whose designator is unknown to the responder.
0x0052	START_OFFSET_NOT_SUPPORTED	Proposed transfer with explicit start offset is not supported in current context.
0x0053	VERSION_NOT_SUPPORTED	Could not find a common supported version between initiator and responder.
0x005F	UNKNOWN	Other unexpected error.

The following **StatusReport** message **ProtocolCode** values MAY occur at any time in response to any BDx message:

- **UNEXPECTED_MESSAGE**: When a peer receives a well-formed message that was contextually inappropriate for the current state of the transfer. For example, receiving a **Block** message before a **SendAccept** message, or other logical inconsistencies.
- **BAD_MESSAGE_CONTENTS**: When a peer receives a malformed protocol message.
- **TRANSFER_FAILED_UNKNOWN_ERROR**: Other error occurred, such as perhaps an input/output error occurring at either peer.