

transfer followed by the re-opening of a new one with a different **STARTOFS** field specified.

In asynchronous transfers, no **BlockQueryWithSkip** messages are sent.

The fields of the **BlockQueryWithSkip** message are:

Table 118. *BlockQueryWithSkip* message fields

Field	Size	Notes
Message ID: BlockQueryWithSkip(0x15)		
BlockCounter	4 octets	Unsigned little-endian
BytesToSkip	8 octets	Unsigned little-endian

11.22.6.4. Block Message

The **Block** message is the container for the actual bulk transfer data.

Blocks SHALL be sent ascending and sequential block counter order (see [Section 11.22.6.1](#), “**Block Ordering Rules**”). Block data payload length does not need to exactly match the Max Block Size for the transfer.

The fields of the **Block** message are:

Table 119. *Block* message fields

Field	Size	Notes
Message ID: Block(0x11)		
Block Counter	4 octets	Unsigned little-endian
Data	Variable Length	- The data field’s length is that of the remainder of the message payload after the Block Counter field, since Matter messages have definite length. - The length SHALL be in the range $[0 < \text{Length} \leq \text{Max Block Size}]$, where Max Block Size is the negotiated Max Block Size matching the SendAccept / ReceiveAccept message that initiated the transfer.

11.22.6.5. BlockEOF Message

The **BlockEOF** message represents the final block in a data transfer.

Note that, unlike a **Block**, **BlockEOF** MAY have a data length of zero. If the entire transfer fits within the negotiated block size, the **BlockEOF** SHALL be the one and only message sent in the exchange and no **Block** messages will be sent. In that trivial case, the Block Counter would be 0 in the **BlockEOF**.

On receipt of this message, the recipient SHALL verify that the pre-negotiated file size was trans-