

The schema is presented in the table below:

Name	Type	Constraint	Conformance	Mutable
VendorID	vendor-id	all	M	No
ProductID	uint16	all	desc	No
IsPAA	bool	all	M	No
Label	string	max 64	M	No
CRLSignerDelegator	string	max 2048	desc	Yes
CRLSignerCertificate	string	max 2048	M	Yes
IssuerSubjectKeyID	string	max 64	M	No
DataUrl	string	max 256	M	Yes
DataFileSize	uint64	desc	O	Yes
DataDigest	string	max 128	desc	Yes
DataDigestType	uint32	all	desc	Yes
RevocationType	uint32	desc	M	No
SchemaVersion	uint16	all	M	Yes

11.23.9.1. VendorID

This field SHALL indicate the [VendorID](#) associated with the PAA or PAI whose revocation information is provided. For a non-vendor-scoped PAA, this SHALL be the VendorID associated with the organization operating the PAA. For vendor-scoped PAA and for PAIs, this field SHALL contain the VendorID as found in the CRLSignerCertificate (see [Section 6.2.2.2, “Encoding of Vendor ID and Product ID in subject and issuer fields”](#) for encoding).

11.23.9.2. ProductID

This field is only required when a PAI is making the distribution point available. This field SHALL only be provided if the IsPAA field is false and if the CRLSignerCertificate field has a ProductID in its subject (see [Section 6.2.2.2, “Encoding of Vendor ID and Product ID in subject and issuer fields”](#) for encoding).

11.23.9.3. IsPAA

This field SHALL be set to true if the revocation information distribution point relates to a PAA, otherwise it SHALL be set to false (i.e. it relates to a PAI, not a PAA)."

11.23.9.4. Label

This field contains a label to disambiguate multiple revocation information partitions of a particular issuer. Uniqueness within the Device Attestation PKI Revocation Distribution Points schema