

Information Entry.

- A. Add any missing entries to the GroupIDList of the Endpoint Information Entry.
 - B. For any entries in the GroupIDList with Status of **Pending**:
 - I. Add the corresponding change to the Node's Group List.
 1. If successful, mark the Status to **Committed**.
 2. If not successful, update the Status to **CommitFailed** and the FailureCode to the returned error. The error SHALL be handled in a subsequent **Node Refresh**.
 - C. For any entries in the GroupIDList with Status of **DeletePending**:
 1. If successful, remove the corresponding entry from the Node's Group List.
 2. If not successful, update the Status to **CommitFailed** and the FailureCode to the returned error. The error SHALL be handled in a subsequent **Node Refresh**.
 - D. For any entries in the GroupIDList with Status of **CommitFailure**:
 - I. A **CommitFailure** with an unrecoverable FailureCode SHALL be handled by removing the entry from the GroupIDList.
 - II. A **CommitFailure** with a recoverable FailureCode (i.e. **TIMEOUT**, **BUSY**) SHALL be handle in a subsequent **Node Refresh**.
- ii. Check that each entry in Node's Binding List occurs in the BindingList of the Endpoint Information Entry.
- A. Add any missing entries to the BindingList of the Endpoint Information Entry.
 - B. For any entries in the BindingList with Status of **Pending**:
 - I. Add the corresponding change to the Node's Binding List.
 1. If successful, mark the Status to **Committed**.
 2. If not successful, update the Status to **CommitFailed** and the FailureCode to the returned error. The error SHALL be handled in a subsequent **Node Refresh**.
 - C. For any entries in the BindingList with Status of **DeletePending**:
 1. If successful, remove the corresponding entry from the Node's BindingList.
 2. If not successful, update the Status to **CommitFailed** and the FailureCode to the returned error. The error SHALL be handled in a subsequent **Node Refresh**.
 - D. For any entries in the BindingList with Status of **CommitFailure**:
 - I. A **CommitFailure** with an unrecoverable FailureCode SHALL be handled by removing the entry from the BindingList.
 - II. A **CommitFailure** with a recoverable FailureCode (i.e. **TIMEOUT**, **BUSY**) SHALL be handle in a subsequent **Node Refresh**.
4. Ensure the GroupKeySetList for the Node Information Entry with the given NodeID matches the Group Keys on the given Node. This involves the following steps:
- a. Read the Group Keys from the Node.
 - b. For each GroupKeySetEntry in the GroupKeySetList of the Node Information Entry with a **Pending** Status: