

11.24.7.15. AddGroupIDToEndpointForNode Command

This command SHALL be used to add a Group ID to an endpoint for a node in the [Joint Fabric](#) Datastore Cluster of the accessing fabric.

The data for this command is as follows:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	NodeID	node-id	all			M
1	EndpointID	endpoint-no	all			M
2	GroupID	group-id	all			M

GroupID represents the unique identifier for the group to be added to the endpoint.

EndpointID represents the unique identifier for the endpoint to be updated in the [Joint Fabric](#) Datastore Cluster.

NodeID represents the unique identifier for the node to which the endpoint belongs.

Upon receipt of this command, the Datastore SHALL:

1. Confirm that an Endpoint Information Entry exists for the given NodeID and EndpointID, and if not, return NOT_FOUND.
2. Ensure the Group Key List for the Node Information Entry with the given NodeID includes the KeySet for the given Group ID. If it does not:
 - a. Add an entry for the KeySet of the given Group ID to the Group Key List for the Node. The new entry's status SHALL be set to **Pending**.
 - b. Add a Group Key Entry for this KeySet to the given Node ID.
 - i. If this succeeds, update the new KeySet entry in the Datastore to **Committed**.
 - ii. If not successful, the pending change SHALL be applied in a subsequent [Node Refresh](#).
3. Ensure the Group List for the Endpoint Information Entry with the given NodeID and EndpointID includes an entry for the given Group. If it does not:
 - a. Add a Group entry for the given Group ID to the Group List for the Endpoint and Node. The new entry's status SHALL be set to **Pending**.
 - b. Add this Group entry to the given Endpoint ID on the given Node ID.
 - i. If this succeeds, update the new Group entry in the Datastore to **Committed**.
 - ii. If not successful, update the Status to **CommitFailed** and the FailureCode to the returned error. The error SHALL be handled in a subsequent [Node Refresh](#).

11.24.7.16. RemoveGroupIDFromEndpointForNode Command

This command SHALL be used to remove a Group ID from an endpoint for a node in the [Joint Fabric](#) Datastore Cluster of the accessing fabric.