

11.25.7. Commands

ID	Name	Direction	Response	Access	Conformance
0x00	ICACSRRequest	client ⇒ server	ICACSRResponse	A	P, M
0x01	ICACSRResponse	client ⇐ server	N		P, M
0x02	AddICAC	client ⇒ server	ICACResponse	A	P, M
0x03	ICACResponse	client ⇐ server	N		P, M
0x04	OpenJoint-CommissioningWindow	client ⇒ server	Y	A	P, M
0x05	TransferAnchorRequest	client ⇒ server	TransferAnchorResponse	A	P, M
0x06	TransferAnchorResponse	client ⇐ server	N	A	P, M
0x07	TransferAnchorComplete	client ⇒ server	Y	A	P, M
0x08	Announce-JointFabricAdministrator	client ⇒ server	Y	A	P, M

11.25.7.1. ICACSRRequest Command

This command SHALL be generated during [Joint Commissioning Method](#) and subsequently be responded in the form of an [ICACSRResponse](#) command.

Effect on Receipt

This command SHALL be received over a [CASE](#) session otherwise it SHALL fail with an INVALID_COMMAND status code.

If this command is received without an armed fail-safe context (see [Section 11.10.7.2, “ArmFail-Safe”](#)), then this command SHALL fail with a FAILSAFE_REQUIRED status code sent back to the initiator.

If the [FabricFabric Table Vendor ID Verification Procedure](#) has not been executed against the initiator of this command, the command SHALL fail with a [JfVidNotVerified](#) status code SHALL be sent back to the initiator.

If a prior AddICAC command was successfully executed within the fail-safe timer period, then this command SHALL fail with a CONSTRAINT_ERROR status code sent back to the initiator.

11.25.7.2. ICACSRResponse Command

This command SHALL be generated in response to a [ICACSRRequest](#) command.