

Chapter 12. Multiple Fabrics

12.1. Introduction

The Multiple Fabric feature allows a Node to be commissioned to multiple separately-administered Fabrics. With this feature a current Administrator can (with user consent) allow the Commissioner for another fabric to commission that Node within its Fabric. The new Commissioner SHALL have their own [Node Operational Certificate \(NOC\)](#) issued by its Trusted Root Certificate Authority (TRCA). Once commissioning is completed and the Node is properly configured, Administrators on the newly joined Fabric have access to the Node and can perform all administrative tasks.

A Fabric is anchored by its Trusted Root Certificate Authority (TRCA). A TRCA MAY delegate to one or more Intermediate Certificate Authorities (ICA) which issue [NOCs](#). Multiple vendors or companies can use the same CA hierarchy in which case they will be governed under the same Trusted Root Certificate Authority.

12.2. Joint Fabric

12.2.1. Introduction

When multiple vendors or companies use the same CA hierarchy, governed under the same Trusted Root Certificate Authority, they create a Joint Fabric using the [Joint Commissioning Method](#) flow. This flow enables a set of one or more companies to use a single fabric anchored by the Trusted Root Certificate Authority (TRCA). In the context of [JCM](#), the fabric that is anchored by this TRCA is known as the Anchor Fabric.

NOTE Support for Joint Fabric is provisional.

12.2.2. Node ID Generation

Any newly-allocated Node ID SHALL:

- be greater than 0x0000_0000_0000_0000, but less than 0xFFFF_FFEF_FFFF_FFFF, representing a value within the Operational NodeID range (see [Table 4, “Node Identifier Allocations”](#));
- be checked to ensure its uniqueness in the [NodeList](#) attribute of the [Section 12.2, “Joint Fabric”](#) Datastore

The Node ID SHALL be regenerated if these constraints are not met.

It is RECOMMENDED to use random allocation within the valid range to avoid having to regenerate the Node ID.

12.2.3. Anchor ICAC requirements

The Anchor ICAC SHALL be the ICAC corresponding to the Anchor Administrator. The Anchor ICAC SHALL contain the reserved [org-unit-name](#) attribute from the [Table 85, “Standard DN Object Identifiers”](#) with value [jf-anchor-icac](#) in its Subject DN. The Anchor ICAC SHALL be issued only by the