

Bridged Node Endpoint(s)

Every Bridged Node endpoint presented that conforms to the FabricSynchronizedNode condition (see Device Library, *Bridged Node*) represents a device that can be synchronized (A Synchronized Device).

The Bridged Node with FabricSynchronizedNode condition enables the synchronization of devices between fabrics by the following:

- The Bridged Node SHALL include the Ecosystem Information Cluster. (Enables discovery and directory synchronization.)
- The Bridged Node SHALL include the Administrator Commissioning Cluster when the user consents to share a device. (Enables synchronization of devices between fabrics.)
- The Bridged Node SHOULD support the BridgedICDSupport feature in the Bridged Device Basic Information Cluster if the Synchronized Device is an Intermittently Connected Device (ICD). (Enables communication with ICDs.)

12.6.4. Preventing Device Duplication

A Fabric Synchronizing Administrator SHOULD NOT commission devices onto the same fabric that they are already on. To avoid this, the Fabric Synchronizing Administrator SHOULD examine the UniqueID of a potential Synchronized Device's Bridged Device Basic Information Cluster and SHOULD examine the VendorID and ProductID fields if they are present in the Bridged Device Basic Information Cluster. If all of the provided values for UniqueID, ProductID, and VendorID match a known device that is already on the Fabric Synchronizing Administrator's fabric, then it SHOULD NOT attempt to commission the device.

12.6.4.1. Missing UniqueID

The UniqueID field in the Basic Information Cluster became mandatory after the initial release of this specification. Therefore, the following must be performed to support devices without UniqueIDs.

When a Fabric Synchronizing Administrator commissions a Synchronized Device, it SHALL persist and maintain an association with the UniqueID in the Bridged Device Basic Information Cluster exposed by another Fabric Synchronizing Administrator.

If a Fabric Synchronizing Administrator exposes a Synchronized Device which does not have a UniqueID in its Basic Information Cluster, then the Fabric Synchronizing Administrator SHALL generate and persist a new UniqueID to be used in the Bridged Device Basic Information Cluster.

12.6.4.2. Unifying Generated UniqueID

When a Fabric Synchronizing Administrator establishes a PASE session to a Synchronized Device for the purposes of commissioning, the Fabric Synchronizing Administrator SHOULD verify that the device is not already present on the intended fabric as follows:

- The Fabric Synchronizing Administrator MAY check if the UniqueID is present in the Basic Information Cluster. If the UniqueID is present, the Fabric Synchronizing Administrator can