

ID	Description
CM183	VID & PID are not advertised before Commissioning.
CM199	Light client cryptographically verifies responses received from nodes.
CM244	Commissioners and Administrators carefully control which Nodes get Administer, Manage, or Operate privilege, especially for safety-critical systems like Door Locks and Smoke CO Alarms.
CM245	Device manufacturers consider carefully whether their products that support remotely starting its operation could do harm to the end user; if so, require some additional operations (e.g. attended confirmation for remote start).
CM248	Devices with content launching features require source of content origin and perform verification of origin information and display human-friendly information before sharing Video content and/or commands to perform sharing of content
CM249	The Screen device and content sharing client support implementing the minimum required WebRTC security requirements as stated in w3c and webrtc-security WebRTC security requirements (see https://www.w3.org/TR/webrtc/#privacy-and-security-considerations and https://webrtc-security.github.io)
CM250	The commissioner require utilizing ACL or similar access control mechanisms for uniquely identifying and controlling access by Video content-sharing clients so that access control can be managed and revoked without impacting the primary device admin account
CM251	Devices supporting content control functionality will enforce the required parental controls specific to the content being shared and inform the user of limitations of this control, for example, when these settings do not apply to content provided by Content Apps on the TV
CM252	The Screen device provide access using dynamic passcode or user-defined passphrase (similar to other casting protocols) with options to reset frequently
CM253	Detect and surface to the user suspicious behavior by unauthenticated network clients and provide the user with the option to disable any information or functionality exposed to unauthenticated clients
CM254	Treat unauthenticated data as advisory only
CM259	Include the ability to revoke an Operational Certificate
CM263	Device reverts to safe state before performing unsafe operations and in case of outage
CM269	Device vets settings that could lead to a safety or physical impact and ignores if outside safe limits.
CM272	Products implement widely agreed Product Security best practices.
CM276	The Commissioner or Administrator completing the commissioning, after the first phase has been executed using NFC-based commissioning, SHALL actively inform a user about devices not appearing on the operational network in the second phase, allowing a user to detect potential re-commissioning over NFC by unauthorized users.