

### 14.3.3. TLS Minimum Requirements

This section describes the minimum requirements when supporting the various TLS clusters.

#### 14.3.3.1. Minimum storage for TLS Certificates

Nodes SHALL provide enough storage space for at least 5 Root certificates per Fabric on a Node. Certain device types MAY choose to increase this minimum.

Nodes SHALL provide enough storage space for at least 2 Client Certificate Details per Fabric on a Node. Certain device types MAY choose to increase this minimum.

#### 14.3.3.2. Minimum storage for TLS Endpoints

Nodes SHALL provide enough storage to provision at least 2 TLS Endpoints per Fabric. Certain device types MAY choose to increase this minimum. In addition, Nodes SHALL be capable of at least 2 concurrent TLS client connections per Fabric using the provisioned TLS Endpoints.

## 14.4. TLS Certificate Management Cluster

This cluster is used to manage TLS CA Root and Client Certificates on a Node, which are then used by other clusters to provision and manage their usage of TLS.

Commands in this cluster uniformly use the [Large Message](#) qualifier, even when the command doesn't require it, to reduce the testing matrix.

This cluster SHALL be present on the [root node endpoint](#) when required by a device type, MAY be present on that endpoint otherwise, and SHALL NOT be present on any other Endpoint of any Node.

### 14.4.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

| Revision | Description     |
|----------|-----------------|
| 1        | Initial Release |

### 14.4.2. Classification

| Hierarchy | Role    | Scope | PICS Code |
|-----------|---------|-------|-----------|
| Base      | Utility | Node  | TLSCERT   |

### 14.4.3. Cluster ID

| ID     | Name                       |
|--------|----------------------------|
| 0x0801 | TLS Certificate Management |