

ID	Name	Direction	Response	Access	Quality	Conformance
0x0E	Remove-ClientCertificate	client ⇒ server	Y	A F	L	M

14.4.6.1. ProvisionRootCertificate Command

This command SHALL provision a newly provided certificate, or rotate an existing one, based on the contents of the CAID field.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Certificate	octstr	max 3000			M
1	CAID	TLSCAID	all	X		M

Certificate Field

This field SHALL be an octet string that represents a certificate encoded using DER encoding.

CAID Field

This field SHALL be a [TLSCAID](#) representing the unique Certificate Authority ID. A null requests a new certificate to be added, and a non-null allows for updating / rotating an existing certificate.

Effect on Receipt

The following process SHALL be followed when the server receives this command:

- If the [UTCTime](#) attribute of the [Time Synchronization](#) cluster is null:
 - Fail the command with the status code INVALID_IN_STATE, and end processing with no other side effects.
- If the passed in *Certificate* is an invalid [TLS Certificate](#):
 - Fail the command with the status code DYNAMIC_CONSTRAINT_ERROR, and end processing with no other side effects.
- If any existing entry for Certificate is found in [ProvisionedRootCertificates](#) which has both a matching Fingerprint and an [associated fabric](#) which matches the [accessing fabric](#):
 - Fail the command with the status code ALREADY_EXISTS, and end processing with no other side effects.
- If the passed in *CAID* is null:
 - If the count of entries in the [ProvisionedRootCertificates](#) list where the [associated fabric](#) matches the [accessing fabric](#), is equal to the [MaxRootCertificates](#) value:
 - Fail the command with the status code RESOURCE_EXHAUSTED, and end processing with no other side effects.