

14.4.6.5. LookupRootCertificate Command

This command SHALL return the [CAID](#) for the passed in fingerprint.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Fingerprint	octstr	max 64			M

Fingerprint Field

This field SHALL be an octet string that represents the [certificate fingerprint](#).

Effect on Receipt

The following process SHALL be followed when the server receives this command:

- If the [ProvisionedRootCertificates](#) list is empty:
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- If there is no entry in the [ProvisionedRootCertificates](#) list that has a matching [Fingerprint](#), or the [associated fabric](#) of that entry does not equal the [accessing fabric](#):
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- Return the [CAID](#) of that entry, in the corresponding [LookupRootCertificateResponse](#) command.

14.4.6.6. LookupRootCertificateResponse Command

This command SHALL be generated in response to a LookupRootCertificate command.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	CAID	TLSCAID	0 to 65534			M

CAID Field

This field SHALL be a [TLSCAID](#) representing the unique Certificate Authority ID.

14.4.6.7. RemoveRootCertificate Command

This command SHALL be generated to request the server removes the certificate provisioned to the provided Certificate Authority ID.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	CAID	TLSCAID	0 to 65534			M