

command.

Note: If an entry in the returned list has an empty [ClientCertificate](#) field, it means the [ClientCSR](#) command was invoked, but the corresponding [ProvisionClientCertificate](#) has not been invoked yet.

14.4.6.12. FindClientCertificateResponse Command

This command SHALL be generated in response to a FindClientCertificate command.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	CertificateDetails	list[TLSClientCertificateDetailStruct]	1 to Max-ClientCertificates			M

CertificateDetails Field

This field SHALL be a list of [TLSClientCertificateDetailStruct](#) containing a minimum of one entry.

14.4.6.13. LookupClientCertificate Command

This command SHALL return the CCDID for the passed in Fingerprint.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Fingerprint	octstr	max 64			M

Fingerprint Field

This field SHALL be an octet string that represents the [certificate fingerprint](#).

Effect on Receipt

The following process SHALL be followed when the server receives this command:

- If the [ProvisionedClientCertificates](#) list is empty:
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- If there is no entry in the [ProvisionedClientCertificates](#) list that has a [Fingerprint](#) matching the passed in *Fingerprint*:
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- If the [associated fabric](#) of that entry does not equal the [accessing fabric](#):
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- Return the [CCDID](#) field of the matching entry, as the [CCDID](#) field in the corresponding [Lookup-](#)