

Effect on Receipt

The following process SHALL be followed when the server receives this command:

- If the **UTCTime** attribute of the **Time Synchronization** cluster is null:
 - Fail the command with the cluster-specific status code of **InvalidTime**, and end processing with no other side effects.
- If there is no entry for the passed in **CAID** in the **ProvisionedRootCertificates** list:
 - Fail the command with the cluster-specific status code of **RootCertificateNotFound**, and end processing with no other side effects.
- If the **associated fabric** for that matching entry, does not equal the **accessing fabric**:
 - Fail the command with the cluster-specific status code of **RootCertificateNotFound**, and end processing with no other side effects.
- If the passed in **CCDID** is not NULL, and the **associated fabric** for the passed in **CCDID** entry in the **ProvisionedClientCertificates** list does not equal the **accessing fabric**:
 - Fail the command with the cluster-specific status code of **ClientCertificateNotFound**, and end processing with no other side effects.
- If the passed in **EndpointID** is NULL:
 - If the length of **ProvisionedEndpoints** is equal to the **MaxProvisioned** value:
 - Fail the command with the status code **RESOURCE_EXHAUSTED**, and end processing with no other side effects.
 - If there is an existing entry for the **Hostname** / **Port** combination in the **ProvisionedEndpoints** list, where the **associated fabric** equals the **accessing fabric**:
 - Fail the command with the cluster-specific status code of **EndpointAlreadyInstalled**, and end processing with no other side effects.
 - Generate a new **TLSEndpointID**
 - Create and populate a **TLSEndpointStruct** with the passed in values, associated with the **accessing fabric**
 - Set the **EndpointID** field to the newly generated **TLSEndpointID**.
 - Set the **ReferenceCount** field to 0.
 - Add the resulting **TLSEndpointStruct** to the **ProvisionedEndpoints** list and store the results.
- Else if the passed in **EndpointID** is not NULL:
 - If there is no entry found for the passed in **EndpointID** in the **ProvisionedEndpoints** list:
 - Fail the command with the status code **NOT_FOUND**, and end processing with no other side effects.
 - If the **associated fabric** for that matching entry does not equal the **accessing fabric**:
 - Fail the command with the status code **NOT_FOUND**, and end processing with no other side effects.
 - Update the fields of that matching entry with the passed in values and store the results.