

Table 125. Sample encoding of primitive types

| Type and Value                                                  | Encoding (hex)             |
|-----------------------------------------------------------------|----------------------------|
| Boolean <b>false</b>                                            | 08                         |
| Boolean <b>true</b>                                             | 09                         |
| Signed Integer, 1-octet, value <b>42</b>                        | 00 2a                      |
| Signed Integer, 1-octet, value <b>-17</b>                       | 00 ef                      |
| Unsigned Integer, 1-octet, value <b>42U</b>                     | 04 2a                      |
| Signed Integer, 2-octet, value <b>42</b>                        | 01 2a 00                   |
| Signed Integer, 4-octet, value <b>-170000</b>                   | 02 f0 67 fd ff             |
| Signed Integer, 8-octet, value <b>40000000000</b>               | 03 00 90 2f 50 09 00 00 00 |
| UTF-8 String, 1-octet length, <b>"Hello!"</b>                   | 0c 06 48 65 6c 6c 6f 21    |
| UTF-8 String, 1-octet length, <b>"Tschüs"</b>                   | 0c 07 54 73 63 68 c3 bc 73 |
| Octet String, 1-octet length, octets <b>00 01 02 03 04</b>      | 10 05 00 01 02 03 04       |
| Null                                                            | 14                         |
| Single precision floating point <b>0.0</b>                      | 0a 00 00 00 00             |
| Single precision floating point (1.0 / 3.0)                     | 0a ab aa aa 3e             |
| Single precision floating point <b>17.9</b>                     | 0a 33 33 8f 41             |
| Single precision floating point infinity ( $\infty$ )           | 0a 00 00 80 7f             |
| Single precision floating point negative infinity ( $-\infty$ ) | 0a 00 00 80 ff             |
| Double precision floating point <b>0.0</b>                      | 0b 00 00 00 00 00 00 00 00 |
| Double precision floating point (1.0 / 3.0)                     | 0b 55 55 55 55 55 55 d5 3f |
| Double precision floating point <b>17.9</b>                     | 0b 66 66 66 66 66 e6 31 40 |
| Double precision floating point infinity ( $\infty$ )           | 0b 00 00 00 00 00 00 f0 7f |
| Double precision floating point negative infinity ( $-\infty$ ) | 0b 00 00 00 00 00 00 f0 ff |

Table 126, “Sample encoding of containers” shows sample encodings for container types. In each of the examples below, the outermost container is encoded as an anonymous element.

Table 126. Sample encoding of containers

| Type and Value                                                                                 | Encoding (hex)          |
|------------------------------------------------------------------------------------------------|-------------------------|
| Empty Structure, <b>{}</b>                                                                     | 15 18                   |
| Empty Array, <b>[]</b>                                                                         | 16 18                   |
| Empty List, <b>[]</b>                                                                          | 17 18                   |
| Structure, two context specific tags, Signed Integer, 1 octet values, <b>{0 = 42, 1 = -17}</b> | 15 20 00 2a 20 01 ef 18 |