

Type and Value	Encoding (hex)
Array, Signed Integer, 1-octet values, [0, 1, 2, 3, 4]	16 00 00 00 01 00 02 00 03 00 04 18
List, mix of anonymous and context tags, Signed Integer, 1 octet values, [[1, 0 = 42, 2, 3, 0 = -17]]	17 00 01 20 00 2a 00 02 00 03 20 00 ef 18
Array, mix of element types, [42, -170000, {}, 17.9, "Hello!"]	16 00 2a 02 f0 67 fd ff 15 18 0a 33 33 8f 41 0c 06 48 65 6c 6c 6f 21 18

Table 127, “Sample encoding of different tag types” shows sample encoding of a value with different associated tags, using Vendor ID = : 65522 (0xFF2), one of the [Vendor IDs allocated for testing purposes](#).

Table 127. Sample encoding of different tag types

Type and Value	Encoding (hex)
Anonymous tag, Unsigned Integer, 1-octet value, 42U	04 2a
Context tag 1, Unsigned Integer, 1-octet value, 1 = 42U	24 01 2a
Common profile tag 1, Unsigned Integer, 1-octet value, Matter::1 = 42U	44 01 00 2a
Common profile tag 100000, Unsigned Integer, 1-octet value, Matter::100000 = 42U	64 a0 86 01 00 2a
Fully qualified tag, Vendor ID 0xFFF1/65521, profile number 0xDEED/57069, 2-octet tag 1, Unsigned Integer, 1-octet value 42, 65521::57069:1 = 42U	c4 f1 ff ed de 01 00 2a
Fully qualified tag, Vendor ID 0xFFF1/65521, profile number 0xDEED/57069, 4-octet tag 0xAA55FEED/2857762541, Unsigned Integer, 1-octet value 42, 65521::57069:2857762541 = 42U	e4 f1 ff ed de ed fe 55 aa 2a
Structure with the fully qualified tag, Vendor ID 0xFFF1/65521, profile number 0xDEED/57069, 2-octet tag 1. The structure contains a single element labeled using a fully qualified tag under the same profile, with 2-octet tag 0xAA55/43605. 65521::57069:1 = {65521::57069:43605 = 42U}	d5 f1 ff ed de 01 00 c4 f1 ff ed de 55 aa 2a 18