

A particular **FIELD GROUP** SHALL NOT be included more than once within a given **STRUCTURE**.

The names assigned to fields within an included **FIELD GROUP** SHALL be distinct with respect to all other fields contained within the enclosing **STRUCTURE**, whether defined directly within the **STRUCTURE** itself, or included from another **FIELD GROUP**.

Likewise, tags assigned to fields within an included **FIELD GROUP** SHALL be distinct with respect to all other fields within the enclosing **STRUCTURE**.

B.4. Pseudo-Types

Pseudo-types are type-like constructs that provide flexibility in schema definitions. Some pseudo-types, like **CHOICE OF** and **ANY**, allow for variance in the fundamental TLV types that may appear in an encoding. Others make it easier to reuse schema constructs in multiple contexts.

B.4.1. ANY

ANY Syntax

```
ANY
```

ANY declares an element that can be encoded as any fundamental TLV type. Note that **ANY** is not a fundamental TLV type itself, but rather a pseudo-type that identifies a range of possible encodings. An **ANY** type serves a shorthand for (and is exactly equivalent to) a **CHOICE OF** all possible fundamental types.

There are no qualifiers that can be associated with an **ANY** type.

ANY Example

```
app-defined-metadata => ANY
```

B.4.2. CHOICE OF

CHOICE OF Syntax

```
CHOICE [ qualifier ] OF { alternates }
```

```
qualifier (optional):
```

```
    nullable
```

```
alternates:
```

```
    alternate
```

```
    alternates, alternate
```

```
alternate:
```

```
    type-or-ref
```

```
// unnamed alternate
```