

CHOICE OF Invalid Alternates Merge Example

```
CHOICE OF {  
  CHOICE OF {  
    foo: STRING,  
    bar: UNSIGNED INTEGER  
  },  
  CHOICE OF {  
    foo: BOOLEAN,  
    bar: FLOAT64  
  }  
}
```

The example below shows how a valid schema should look to avoid conflict:

CHOICE OF Valid Alternates Merge Example

```
CHOICE OF {  
  alt1: CHOICE OF {  
    foo: STRING,  
    bar: UNSIGNED INTEGER  
  },  
  alt2: CHOICE OF {  
    foo: BOOLEAN,  
    bar: FLOAT64  
  }  
}
```

B.4.2.3. Ambiguous Alternates

A **CHOICE OF** MAY contain multiple alternates having the same fundamental TLV type (e.g. two alternates that are both **SIGNED INTEGER**). If these alternates are also encoded using the same tag, their encoded forms are effectively indistinguishable from one another. Such alternates are referred to as ambiguous alternates.

Ambiguous alternates MAY occur due to the merging of nested **CHOICE OF** definitions (see above). They MAY also arise in cases where the tags associated with the alternates are overridden by a tag qualifier in an outer context; e.g. when a **STRUCTURE** incorporates a **CHOICE OF** field that has a specific tag qualifier assigned to the field.

Ambiguous alternates are legal in TLV Schemas. However, care SHALL be taken when introducing ambiguous alternates to ensure that a decoder can correctly interpret the resulting encoding. This can be achieved, for example, by signaling the appropriate interpretation via a data value (e.g. an enumerated integer) contained elsewhere in the encoding.