

Appendix D: Status Report Messages

D.1. Overview

The **StatusReport** is a core message that encapsulates the result of an operation which a responder sends as a reply for requests sent from an initiator, using a common message of the **Secure Channel Protocol** (Protocol ID = **PROTOCOL_ID_SECURE_CHANNEL**).

This section details the standard Status Report message format encoding as Matter Message Format payloads.

D.2. Status Report elements

A Status Report message describes a protocol-specific operation result or status.

The Status Report message SHALL have the following message header values (some of which may be omitted within protocol messages, as per header flag rules), no matter which protocol actually generated the status report:

- A **Protocol Vendor ID** set to 0 (Matter common Vendor ID)
- A **Protocol ID** set to 0x0000 (**PROTOCOL_ID_SECURE_CHANNEL**)
- A **Protocol Opcode** set to 0x40 (**StatusReport**)

The report message’s **Application Payload** SHALL consist of:

- A mandatory *GENERAL CODE* field, providing a general description of the status being reported.
- A mandatory *PROTOCOL SPECIFIC STATUS* field, providing additional details
- An **optional** protocol-specific data section that MAY include any additional information that a protocol requires
 - Individual protocols define the contents of this data section and how it is handled

D.3. Message Format

Length	Octets 0	1
<i>Structure, little-endian</i>		
2 octets	GeneralCode	
4 octets	ProtocolId of Protocol-Specific Status	
	...	
2 octets	ProtocolCode of Protocol-Specific Status	
Variable	Optional ProtocolData for protocol-specific additional details, MAY be empty	