

```

000000f0  82 f9 91 eb 13 ac 5f 9f  ce 94 30 93 19 aa 94 09 | ....._...0.....|
00000100  6c 8c d4 b8 30 03 17 73  61 6d 70 6c 65 5f 76 65 | l...0..sample_ve|
00000110  6e 64 6f 72 5f 72 65 73  65 72 76 65 64 31 30 05 | ndor_reserved10.|
00000120  18 76 65 6e 64 6f 72 5f  72 65 73 65 72 76 65 64 | .vendor_reserved|
00000130  33 5f 65 78 61 6d 70 6c  65 18                               | 3_example.|
0000013a
-> AttestationSignature field of CSRResponse (len 64 bytes):
00000000  87 8e 46 cf fa 83 c8 32  96 eb 27 2e bc 37 1c 1f | ..F....2..'..7..|
00000010  ef ee 6d 69 54 f3 78 9f  d3 d2 27 e1 64 13 d3 d4 | ..miT.x...'..d...|
00000020  75 a6 2f d0 12 b9 19 d9  95 8b c7 3d 7c 63 b3 cc | u./.....=|c..|
00000030  1e f2 b6 2c 18 e0 cc 10  2e d1 ba 4d ac 85 fe ea | ...,.....M....|
00000040

```

F.4. Check-In Protocol test vectors

This subsection contains worked examples of the [Check-In Protocol encryption](#) and [decryption](#).

Test 1

===== Encryption algorithm inputs =====

```

-> Symmetric Key: d9:0e:13:18:0d:00:ba:ad:d2:0c:f5:ed:49:13:d3:ff
-> Server counter: 0c:00:00:00
-> Application data : ''

```

===== Intermediate outputs =====

```

-> generated Nonce: 45:80:d2:c6:f1:31:0d:c4:eb:64:f1:f8:e8
-> Ciphertext: bd:c2:1f:b5
-> Tag: 19:5d:74:7d:d2:87:9b:2b:0d:43:ce:5b:1c:56:50:78

```

===== Encryption algorithm outputs =====

```

-> Check-in message payload :
45:80:d2:c6:f1:31:0d:c4:eb:64:f1:f8:e8:bd:c2:1f:b5:19:5d:74:7d:d2:87:9b:2b:0d:43:ce:5b:1c:56:50:78

```

===== Decryption algorithm inputs =====

```

-> Check-in message payload :
45:80:d2:c6:f1:31:0d:c4:eb:64:f1:f8:e8:bd:c2:1f:b5:19:5d:74:7d:d2:87:9b:2b:0d:43:ce:5b:1c:56:50:78
-> Symmetric Key: d9:0e:13:18:0d:00:ba:ad:d2:0c:f5:ed:49:13:d3:ff
-> Client counter: 0b:00:00:00

```

===== Decryption algorithm outputs =====

```

-> Received counter: 0c:00:00:00

```