

7. If the AddGroupIfIdentifying command was received as unicast and the evaluated status is not SUCCESS, or if the AddGroupIfIdentifying command was received as unicast and the evaluated status is SUCCESS and a response is not suppressed, the server SHALL generate a response with the Status field set to the evaluated status.

1.3.7.7. AddGroupResponse Command

The AddGroupResponse is sent by the Groups cluster server in response to an AddGroup command.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Status	enum8	desc			M
1	GroupID	group-id	min 1			M

1.3.7.7.1. Status Field

This field is set according to the Effect on Receipt section of the AddGroup command.

1.3.7.7.2. GroupID Field

This field is set to the GroupID field of the received AddGroup command.

1.3.7.8. ViewGroupResponse Command

The ViewGroupResponse command is sent by the Groups cluster server in response to a ViewGroup command.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Status	enum8	desc			M
1	GroupID	group-id	min 1			M
2	GroupName	string	max 16			M

1.3.7.8.1. Status Field

This field is according to the Effect on Receipt section of the ViewGroup command.

1.3.7.8.2. GroupID Field

This field is set to the GroupID field of the received ViewGroup command.

1.3.7.8.3. GroupName Field

If the status is SUCCESS, and group names are supported, this field is set to the group name associated with that group in the Group Table; otherwise it is set to the empty string.

1.3.7.9. GetGroupMembershipResponse Command

The GetGroupMembershipResponse command is sent by the Groups cluster server in response to a