

Bit	Code	Feature	Conformance	Summary
0	SN	SceneNames	O	The ability to store a name for a scene.

The following sections describe each feature in some detail. Further details are found within the specification.

1.4.4.1. SceneNames Feature

This feature indicates the ability to store a name for a scene when a scene is added.

1.4.5. Dependencies

Any endpoint that implements the Scenes Management server cluster SHALL also implement the Groups server cluster.

Note that the [RemoveGroup command](#) and the [RemoveAllGroups command](#) of the [Groups cluster](#) also remove scenes.

1.4.6. Handling of fabric-scoping

Attributes and commands for this cluster are scoped to the accessing fabric and SHALL only affect or reflect data related to the accessing fabric, with the exception of the [SceneValid Field](#) of the [FabricSceneInfo](#) attribute.

The following constraints apply in addition to any other stated requirements in individual data model elements:

- Any attribute read, attribute write or command invoked on the server when no accessing fabric is available SHALL fail with a status code of `UNSUPPORTED_ACCESS` returned to the client.
- When accessing scene information, implementations SHALL ensure that scenes with identical Group ID and Scene ID across fabrics will only access the data for the accessing fabric, so that the same identifier values used by different accessing fabrics do not cause mixing or overwriting of another fabric's scenes.
- Upon leaving a fabric with the [RemoveFabric](#) command of the [Operational Credentials Cluster](#), all scenes data for the associated fabric SHALL be removed from the Scene Table.
- The Scene Table capacity for a given fabric SHALL be less than half (rounded down towards 0) of the Scene Table entries (as indicated in the `SceneTableSize` attribute), with a maximum of 253 entries (to allow expressing it in the [GetSceneMembershipResponse](#) command). If the Scene Table capacity is about to be exceeded by adding or storing a scene, then the resource exhaustion behavior of the associated command SHALL apply.

1.4.7. Data Types