

- Attribute 0x4001, EnhancedColorMode, S quality, mandatory, implemented
- Attribute 0x4002, ColorLoopActive, S quality, optional based on feature, NOT implemented
- Attribute 0x4003, ColorLoopDirection, S quality, optional based on feature, NOT implemented
- Attribute 0x4004, ColorLoopTime, S quality, optional based on feature, NOT implemented

An ExtensionFieldSetStruct containing an invalid AttributeValuePairStruct SHALL be considered invalid.

1.4.7.5. Logical Scene Table

The Scene Table is used to store information for each scene capable of being invoked on the server. Each scene is defined for a particular group. The Scene Table is defined here as a conceptual illustration to assist in understanding the underlying data to be stored when scenes are defined. Though the Scene Table is defined here using the data model architecture rules and format, the design is not normative.

The Scene table is logically a list of fabric-scoped structs. The logical fields of each Scene Table entry struct are illustrated below. An ExtensionFieldSetStruct MAY be present for each Scenes-supporting cluster implemented on the same endpoint.

Quality: Fabric Scoped							
ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	Scene-GroupID	group-id	all				M
1	SceneID	uint8	max 254				M
2	Scene-Name	string	max 16				SN
3	Scene-TransitionTime	uint32	max 60000000		0		M
4	Extension-Fields	list[ExtensionFieldSetStruct]			empty		M

1.4.7.5.1. SceneGroupID Field

This field is the group identifier for which this scene applies, or 0 if the scene is not associated with a group.

1.4.7.5.2. SceneID Field

This field is unique within this group, which is used to identify this scene.