

1.4.9.8.1. GroupID Field

This field SHALL indicate the group identifier in the Group Table.

1.4.9.8.2. Effect on Receipt

On receipt of this command, the server SHALL perform the following procedure:

1. If the value of the GroupID field is non-zero, the server verifies that the endpoint has an entry for that GroupID in the Group Table. If there is no such entry in the Group Table, the status SHALL be INVALID_COMMAND and the server continues from step 3.
2. The server SHALL remove all scenes, corresponding to the value of the GroupID field, from its Scene Table and the status SHALL be SUCCESS.
3. If the RemoveAllScenes command was received as a unicast, the server SHALL then generate a RemoveAllScenesResponse command with the Status field set to the evaluated status.

1.4.9.9. RemoveAllScenesResponse Command

This command is sent in response to the [RemoveAllScenes](#) command.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Status	status	desc			M
1	GroupID	group-id	all			M

1.4.9.9.1. Status Field

This field SHALL be set according to the Effect on Receipt section for [RemoveAllScenes](#) command.

1.4.9.9.2. GroupID Field

The GroupID field SHALL be set to the corresponding field of the received [RemoveAllScenes](#) command.

1.4.9.9.3. When Generated

This command is generated in response to a received [RemoveAllScenes](#) command.

1.4.9.10. StoreScene Command

This command will create a new entry for the requested scene.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	GroupID	group-id	all			M
1	SceneID	uint8	max 254			M