

1.4.9.11.2. GroupID Field

The GroupID field SHALL be set to the corresponding field of the received [StoreScene](#) command.

1.4.9.11.3. SceneID Field

The SceneID field SHALL be set to the corresponding field of the received [StoreScene](#) command.

1.4.9.11.4. When Generated

This command is generated in response to a received [StoreScene](#) command.

1.4.9.12. RecallScene Command

This command will cause the specified scene to be recalled.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	GroupID	group-id	all			M
1	SceneID	uint8	max 254			M
2	Transition-Time	uint32	max 60000000	X		O

1.4.9.12.1. GroupID Field

This field SHALL indicate the group identifier in the Group Table.

1.4.9.12.2. SceneID Field

This field SHALL indicate the scene identifier in the Scene Table.

1.4.9.12.3. TransitionTime Field

This field SHALL indicate the transition time of the scene, measured in milliseconds.

1.4.9.12.4. Effect on Receipt

On receipt of this command, the server SHALL perform the following procedure:

1. If the value of the GroupID field is non-zero, the server verifies that the endpoint has an entry for that GroupID in the Group Table. If there is no such entry in the Group Table, the status SHALL be INVALID_COMMAND and the server continues from step 4.
2. The server verifies that the scene entry corresponding to the GroupID and SceneID fields exists in its Scene Table. If there is no such entry in its Scene Table, the status SHALL be NOT_FOUND and the server continues from step 4.
3. The server retrieves the requested scene entry from its Scene Table. For each other cluster implemented on the endpoint, it SHALL retrieve any corresponding extension field sets from the Scene Table and set the attributes and corresponding state of the cluster accordingly. If there is no extension field set for a cluster, the state of that cluster SHALL remain unchanged. If