

Bit	Code	Feature	Conformance	Summary
2	OFFONLY	OffOnly	[!(LT DF)]	Device supports the OffOnly feature

1.5.4.1. Lighting Feature

This cluster is used for a lighting application.

On receipt of a Level Control cluster command that causes the OnOff attribute to be set to FALSE, the OnTime attribute SHALL be set to 0.

On receipt of a Level Control cluster command that causes the OnOff attribute to be set to TRUE, if the value of the OnTime attribute is equal to 0, the server SHALL set the OffWaitTime attribute to 0.

1.5.4.2. DeadFrontBehavior Feature

When this feature is supported, the device exposing this server cluster exhibits "dead front" behavior when the "OnOff" attribute is FALSE (Off). This "dead front" behavior includes:

- clusters other than this cluster that are also exposed MAY respond with failures to Invoke and Write interactions. Such failure responses when in a "dead front" SHALL be with an INVALID_IN_STATE status code.
- clusters other than this cluster MAY change the values of their attributes to best-effort values, due to the actual values not being defined or available in this state. Device type specifications that require support for the DF feature SHOULD define what these best-effort values are.
- Report Transactions SHALL continue to be generated. Such transactions MAY include best-effort values as noted above.
- Event generation logic for clusters other than this cluster is unchanged (noting possible use of best-effort attribute values as in the preceding bullets).

When this feature is supported and the OnOff attribute changes from TRUE to FALSE (e.g. when receiving an Off Command, or due to a manual interaction on the device), it SHALL start executing this "dead front" behavior.

When this feature is supported and the OnOff attribute changes from FALSE to TRUE (e.g. when receiving an On Command, or due to a manual interaction on the device), it SHALL stop executing this "dead front" behavior.

When this feature is supported, and any change of the "dead front" state leads to changes in attributes of other clusters due to the "dead front" feature, these attribute changes SHALL NOT be skipped or omitted from the usual processing associated with attribute changes. For example, if an attribute changes from value 4 to null on "dead front" behavior due to an Off command being received, this change SHALL be processed for reporting and subscriptions.

1.5.4.3. OffOnly Feature

When this feature is supported, the [Off](#) command SHALL be supported and the [On](#) and [Toggle](#) com-