

1.5.7.4.3. Effect on Receipt

On receipt of the OffWithEffect command the server SHALL check the value of the GlobalSceneControl attribute.

If the GlobalSceneControl attribute is equal to TRUE, the server SHALL store its settings in its global scene then set the GlobalSceneControl attribute to FALSE, then set the OnOff attribute to FALSE and if the OnTime attribute is supported set the OnTime attribute to 0.

If the GlobalSceneControl attribute is equal to FALSE, the server SHALL only set the OnOff attribute to FALSE.

1.5.7.5. OnWithRecallGlobalScene Command

This command allows the recall of the settings when the device was turned off.

1.5.7.5.1. Effect on Receipt

On receipt of the OnWithRecallGlobalScene command, if the GlobalSceneControl attribute is equal to TRUE, the server SHALL discard the command.

If the GlobalSceneControl attribute is equal to FALSE, the Scenes Management cluster server on the same endpoint SHALL recall its global scene, updating the OnOff attribute accordingly. The OnOff server SHALL then set the GlobalSceneControl attribute to TRUE.

Additionally, when the OnTime and OffWaitTime attributes are both supported, if the value of the OnTime attribute is equal to 0, the server SHALL set the OffWaitTime attribute to 0.

1.5.7.6. OnWithTimedOff Command

This command allows devices to be turned on for a specific duration with a guarded off duration so that SHOULD the device be subsequently turned off, further OnWithTimedOff commands, received during this time, are prevented from turning the devices back on. Further OnWithTimedOff commands received while the server is turned on, will update the period that the device is turned on.

The OnWithTimedOff command SHALL have the following data fields:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	OnOffControl	OnOffControlBitmap	0 to 1			M
1	OnTime	uint16	max 0xFFFE			M
2	OffWaitTime	uint16	max 0xFFFE			M

1.5.7.6.1. OnOffControl Field

This field contains information on how the server is to be operated.