

Revision	Description
2	The MfgCode field was marked non-nullable. Updated the related text. Reorder sections.

1.9.2. Classification

Hierarchy	Role	Scope	PICS Code
Base	Application	Endpoint	MOD

1.9.3. Cluster ID

ID	Name
0x0050	Mode Select

1.9.4. Features

This cluster SHALL support the FeatureMap global attribute:

Bit	Code	Feature	Summary
0	DEPONOFF	OnOff	Dependency with the OnOff cluster

1.9.4.1. OnOff Feature

This feature creates a dependency between an OnOff cluster instance and this cluster instance on the same endpoint. See [Section 1.9.6.6, “OnMode Attribute”](#) for more information.

1.9.5. Data Types

1.9.5.1. SemanticTagStruct Type

A Semantic Tag is meant to be interpreted by the client for the purpose the cluster serves.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	MfgCode	vendor-id	desc	F			M
1	Value	enum16	all	F			M

1.9.5.1.1. Value Field

This field SHALL indicate the semantic tag within a semantic tag namespace which is either manufacturer specific or standard. For semantic tags in a standard namespace, see [Standard Namespace](#).

1.9.5.1.2. MfgCode Field

This field SHALL indicate a manufacturer code (Vendor ID), and the Value field SHALL indicate a